



## Specifications

POWER RATING		125W RMS
NOMINAL DIAMETER		305mm (12")
SENSITIVITY	(1W/1m)	100 dB
RESONANT FREQUENCY	(Fs)	57Hz
DC RESISTANCE	(Re)	7.43Ω
ELECTROMAGNETIC Q	(Qes)	0.51
MECHANICAL Q	(Qms)	2.99
TOTAL Q	(Qts)	0.44
Reference efficiency	(ho)	6.8 %
VOICE COIL DIAMETER		1.5"
OVERHANG	(Xmax)	3 mm
MOVING MASS	(Mms)	29.58.gm
BL PRODUCT	(BL)	12.42 N/Amp
COIL INDUCTANCE	(Le)	0.49 mH
OVERALL DIAMETER		315mm
DEPTH		155 mm
BAFFLE HOLE DIAMETER		284 mm
BOLT MOUNT DIAMETER	(PCD)	304 mm
		8(Bolts)
WEIGHT		5 kg

- 12" dual magnetic field loudspeaker with high continuous power handling capability of 200w RMS.
- Dual magnetic field technology for enhanced flux control, improved efficiency, and reduced distortion.
- Precision die-cast aluminium frame for superior rigidity, excellent heat dissipation, and resonance-free performance.
- Well-balanced, wide spectrum frequency response suitable for professional audio applications.
- High-quality specially designed cone and spider assembly for clear, powerful sound with low distortion.
- High-temperature CCAW voice coil ensuring safe, stable, and reliable operation under demanding conditions.
- Ideal for PA systems, live sound, DJ setups, and professional music applications

